

# CUMMINS

AMi Model	Engine Model	STAMFORD Alternator Model	Gen set Output kVA				Dimensions (mm)			Weight
			50Hz, 3ph (380-400)V		60Hz, 3ph (416-480)V		L	W	H	Kg
			Prime Power	Stdby Power	Prime Power	Stdby Power				
GS 0010 C32S	X1.3-G2	PI 044 E	10	11	N.A.	N.A.	1160	500	1135	479
GS 0024 C32S	X2.5-G2	PI 144 E	24	27	N.A.	N.A.	1400	600	1030	523
GS 0026 C32S	X2.5-G4	PI 144 E	N.A.	N.A.	26	29	1400	600	1030	523
GS 0034 C32S	X3.3-G1	PI 144 H	34	38	N.A.	N.A.	1565	700	1220	622
GS 0037 C32S	X3.3-G2	PI 144 H	N.A.	N.A.	37	40	1565	700	1220	622
GS 0040 C32S	S3.8-G4	PI 144 J	40	44	N.A.	N.A.	1600	600	1230	751
GS 0050 C32S	S3.8-G6	UCI 224 D	50	55	N.A.	N.A.	1675	600	1230	856
GS 0060 C32S	S3.8-G7	UCI 224 E	60	65	N.A.	N.A.	2045	770	1330	992
GS 0100 C32S	6BTA5.9-G5	UCI 274 C	100	106	N.A.	N.A.	2300	800	1450	1188
GS 0120 C32S	6BTA5.9-G6	UCI 274 D	N.A.	N.A.	120	130	2210	820	1580	1209
GS 0106 C32S	6BT5.9-G6	UCI 274 D	106	117	125	130	2100	730	1550	1156
GS 0125 C32S	6BTAA5.9-G3	UCI 274 E	125	135	N.A.	N.A.	2300	700	1550	1254
GS 0150 C32S	QSB7-G3	UCI 274 F	150	175	180	187	2555	865	1510	1409
GS 0200 C32S	QSB7-G5	UCDI 274 J	200	220	225	250	2690	856	1510	1622
GS 0250 C32S	QSL9-G3	UCDI 274 K	250	275	285	310	2625	1065	1770	1911
GS 0300 C32S	QSL9-G5	HCI 444 E	300	345	342	390	2725	1065	1770	2436
GS 0325 C32S	NT855-G6	HCI 444 E	325	360	328	362	3200	1100	2000	3085
GS 0365 C32S	NTA855-G4	HCI 444 F	365	400	N.A.	N.A.	3250	1100	1920	3230
GS 0415 C32S	NTA855-G3	HCI 444 F	N.A.	N.A.	415	445	3250	1100	1920	3230
GS 0465 C32S	QSX15-G6	HCI 544 D	465	510	450	500	3300	1350	2010	3814
GS 0500 C32S	QSX15-G8	HCI 544 E	500	550	450	500	3600	1350	2040	4019
GS 0560 C32S	QSX15-G9	HCI 544 E	N.A.	N.A.	560	625	3750	1250	1995	4001
GS 0635 C32S	VTA28-G5	HCI 544 F	635	700	680	750	3930	1450	2250	5592
GS 0810 C32S	QSK23-G3	HCI 634 H	810	900	920	1015	4440	1660	2280	5802
GS 1000 C32S	QST30-G4	HCI 634 K	1000	1100	1140	1250	4325	2000	2420	7338
GS 1275 C32S	KTA50-G3	PI 734 B	1275	1400	1400	1600	5145	2000	2265	8320
GS 1400 C32S	KTA50-G8	PI 734 C	1400	1650	N.A.	N.A.	5720	2100	3010	10419
GS 1620 C32S	KTA50-G9	PI 734 E	N.A.	N.A.	1620	1900	5870	2100	3010	11004
GS 2000 C32S	QSK60-G4	PI 734 G	2000	2250	N.A.	N.A.	4725	1800	2450	12539
GS 2000 C32S	QSK60-G6	PI 734 G	N.A.	N.A.	2000	2250	4725	1800	2450	12539
GS 2030 C32S	QSK60-G13	PI 734 G	2030	2500	N.A.	N.A.	4725	1800	2450	12539
GS 2750 C32S	QSK78-G9	LV 804 S	2750	3000	N.A.	N.A.	5000	1570	2450	16217
GS 3200 C32S	QSK78-G8	LV 804 T	N.A.	N.A.	3200	3450	5000	1570	2450	16628