

DEUTZ

AMi Model	Engine Model	STAMFORD Alternator Model	Gen set Output kVA				Dimensions			Weight
			50 Hz, 3ph (380- 400 V)		60 Hz, 3ph (416- 480 V)		L	W	H	Kg
			Prime Power	Stdby Power	Prime Power	Stdby Power				
GS 0030 D32S	F3L912	PI 144 G	30	30	34	35	1450	670	1035	657
GS 0040 D32S	F4L912	PI 144 J	40	41	47	48	1750	670	1045	759
GS 0060 D32S	F6L912	UCI 224 E	60	61	67	70	2250	670	1085	1066
GS 0070 D32S	BF4M2012C	UCI 224 F	70	77	80	90	2200	700	1450	1029
GS 0085 D32S	BF4M1013E	UCI 224 G	85	87	91	95	2250	670	1225	1133
GS 0100 D32S	BF4M1013EC	UCI 274 C	100	106	107	112	2300	720	1300	1206
GS 0130 D32S	BF6M1013E	UCI 274 E	130	141	139	145	2750	730	1380	1532
GS 0150 D32S	BF6M1013EC	UCI 274 F	150	165	165	175	2750	865	1530	1620
GS 0175 D32S	BF6M1013FC-G1	UCI 274 G	175	185	200	215	2750	830	1560	1690
GS 0200 D32S	BF6M1013FC-G3	UCDI 274 J	207	226	228	251	2750	850	1620	1847
GS 0230 D32S	BF6M1015	UCDI 274 J	230	250	242	267	3250	1155	1800	2154
GS 0275 D32S	TCD2013L6	HCI 444 D	275	N.A.	282	N.A.	3000	1000	1700	2410
GS 0300 D32S	BF6M1015C-G1	HCI 444 E	316	350	340	374	3260	1550	2200	2744
GS 0350 D32S	BF6M1015C-G2	HCI 444 E	350	370	N.A.	N.A.	3260	1550	2200	2754
GS 0450 D32S	BF8M1015C-G2	HCI 544 C	450	495	N.A.	N.A.	3260	1550	2200	3228
GS 0500 D32S	BF8M1015CP-G3	HCI 544 D	500	515	538	588	3250	1510	2120	3393